17025 SO. MAIN ST. GARDENA, CA 90248 800.572.9029
13238 SO. FIGUEROA ST. LOS ANGELES, CA 90061 stepstoneprecast.com

## **MATERIAL PRODUCT DATA SHEET**

### **Product Name**

Large Scale CalArc Paver

### Manufacturer

 Stepstone, LLC
 Phone
 310-327-7474

 17025 So. Main St.
 Fax
 310-217-1424

 Gardena, CA 90248
 Toll free
 800-572-9029

## **Product Description**

Stepstone has produced high quality precast concrete since 1963. Large Scale CalArc Pavers are precast concrete pavers that are designed for pedestrian use in both commercial and residential applications.

# **Composition & Materials**

Large Scale CalArc Pavers are hand-made, wet-cast from 5000 PSI hard rock concrete using Type III cement.

#### Sizes

Large Scale CalArc Pavers are available in standard sizes ranging from 11-7/8"x11-7/8" to 23-7/8" x 59-7/8" and 2- ½" thickness. See Large Scale CalArc Paver details for standard sizes.

### **Finishes**

Large Scale CalArc Paver available finishes include: Custom aggregates, light, medium, or heavy sandblast

### Colors

Large Scale CalArc Pavers are available in 12 standard colors: Adobe, Agave, Almond, Brick Red, Cafe Brown, Caramel, French Gray, Granada White, Iceberg Green, Kona, Pebble and Porcelain; custom colors are available upon request.

## **Technical Data**

APPLICABLE STANDARDS: American Society for Testing & Materials (ASTM)

ASTM C33 - Standard Specification for Concrete Aggregates

ASTM C39 - Concrete Compressive Strength

ASTM C150 - Standard Specification for Portland Cement

ASTM C642 - Water Absorption, Density, Voids in Hardened Concrete

ASTM C666 - Rapid Freeze/Thaw Resistance of Concrete

ASTM C979 - Pigments for Integrally Colored Concrete

ASTM E303 - Pendulum Slip Resistance

## **Physical / Chemical Properties**

Large Scale CalArc Paver weight is 28 LBS per square foot. Water absorption: Not more than 6.0 % average, not more than 7.0 % for any individual unit for standard colors. Unit length, width and height are not more than +/-1/8" from standard dimensions. No unit will differ more than +/-1/8" from the approved samples. Test reports are available upon request. Concrete is non-combustible.