



17025 SO. MAIN ST. GARDENA, CA 90248 | 800.572.9029
13238 SO. FIGUEROA ST. LOS ANGELES, CA 90061 | stepstoneprecast.com

MATERIAL PRODUCT DATA SHEET

Product Name

Wave Paver

Manufacturer

Stepstone, LLC
17025 So. Main St.
Gardena, CA 90248

Phone 310-327-7474
Fax 310-217-1424
Toll free 800-572-9029

Product Description

Stepstone has produced high quality precast concrete since 1963. Wave Pavers are precast concrete pavers that come in two standard sizes; two shapes per size. Wave Pavers are designed to be used for both commercial and residential applications.

Composition & Materials

Wave Pavers are hand-made, wet-cast from 5000 PSI hard rock concrete using Type III cement.

Sizes

Wave Pavers are available in 2-7/8" x 12" x 4" and 3-7/8" x 12" x 4". Starter pieces available. See Wave Paver details for more size information.

Finishes

Wave Pavers available finishes include: Custom aggregates, light, medium, or heavy sandblast

Colors

Wave Pavers are available in 12 standard colors: Adobe, Agave, Almond, Brick Red, Cafe Brown, Caramel, French Gray, Granada White, Iceberg Green, Kona, Pebble and Porcelain; custom colors are available upon request.

Technical Data

APPLICABLE STANDARDS: American Society for Testing & Materials (ASTM)
ASTM C33 - *Standard Specification for Concrete Aggregates*
ASTM C39 - *Concrete Compressive Strength*
ASTM C150 - *Standard Specification for Portland Cement*
ASTM C642 - *Water Absorption, Density, Voids in Hardened Concrete*
ASTM C666 - *Rapid Freeze/Thaw Resistance of Concrete*
ASTM C979 - *Pigments for Integrally Colored Concrete*
ASTM C1028 - *Coefficient of Friction*

Physical /Chemical Properties

Wave Paver is 48 PSF. Water absorption: Not more than 6.0 % average, not more than 7.0 % for any individual unit for standard colors. Unit length, width and height are not more than +/-1/8" from standard dimensions. No unit will differ more than +/- 1/8" from the approved samples. Test reports are available upon request. Concrete is non-combustible.